

Material Safety Data Sheet

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these data forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

PRODUCT NAME: (25A5) #142 BRITE GALV (AEROSOL) **PRODUCT CODE:** 25A5 **HMIS CODES:** H F R P
PRODUCT USE: GALVANIZED COATING: METALLIC <80% V.O.C. 2 4 1 X

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Aervoe-Pacific Company, Inc.

ADDRESS: 1198 Mark Circle, Gardnerville, NV 89410

EMERGENCY PHONE: 1-800-424-9300

DATE REVISED: 05-24-99

INFORMATION PHONE: (775) 782-0100

NAME OF PREPARER: Mike A. Traquina

REASON REVISED: Updated

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS/WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
*SS-12 XYLENE (CAS 1330 20 7) 17	100 PPM	100 PPM		4300 mg/kg RAT ORAL	6700 PPM; 4hr RAT INHA
SS 41 ACETONE (CAS 67 64 1) 35	750 PPM	750 PPM		9750mg/kg RAT ORAL	N/A
*MP 10 ZINC DUST (CAS 7440 66 6) 12	10 mg/m3	N/A	N/A	N/A	N/A
PR 01A PROPANE (CAS 74 98 6) 15	1000 PPM	1000 PPM		N/A	N/A
PR 01B ISOBUTANE (CAS 75 28 5) <5.0%	800 PPM	800 PPM	<ESTIMATE	N/A	520000 PPM; 2 hr MOUSE EXP
PR 01C NORMAL BUTANE (CAS 106 97 8) 5	600 PPM	600 PPM		N/A	658 mg/L; 4 hr RAT INHA

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

NOTE: N/A applies to not available or not applicable

PRODUCT CODE: 25A5

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: -44° F/-42° C SPECIFIC GRAVITY (H2O=1): 0.8 COEFFICIENT OF WATER/OIL DIST: N/A ODOR THRESHOLD: N/A
VAPOR DENSITY: HEAVIER THAN AIR SOLUBILITY IN WATER: NEGLIGIBLE
EVAPORATION RATE: FASTER THAN n-BUTYL ACETATE APPEARANCE AND ODOR: OPAQUE LIQUID / SOLVENT BASED ODOR
COATING V.O.C.: 5.56 LBS/IMP GAL 4.63 LBS/US GAL 555 GMS/LTR FREEZING POINT: N/A pH: N/A

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: -100° F/-73° C METHOD USED: ESTIMATED FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 1.0% UPPER: 12.8%
EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG
SPECIAL FIREFIGHTING PROCEDURES - WATER SPRAY MAY BE INEFFECTIVE, BUT WATER SPRAY MAY BE USED TO COOL CONTAINERS EXPOSED TO HEAT OR FIRE TO PREVENT PRESSURE BUILD UP.
UNUSUAL FIRE AND EXPLOSION HAZARDS - CLOSED CONTAINERS MAY EXPLODE DUE TO BUILD UP OF PRESSURE FROM EXTREME HEAT OR FIRE. AEROSOL SPRAY IS EXTREMELY FLAMMABLE.
FLAMMABILITY - T.D.G.R. CLASS - CONSUMER COMMODITY ORM-D, (UN1950 CLASS 9), NFPA 308, LEVEL 2 AEROSOL
SENSITIVITY TO IMPACT - DO NOT PUNCTURE SENSITIVITY TO STATIC DISCHARGE - PRIMARILY VAPORS.

SECTION V - REACTIVITY DATA

STABILITY: STABLE CONDITIONS TO AVOID - HIGH TEMPERATURES
INCOMPATIBILITY (MATERIALS TO AVOID) - STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS - CARBON MONOXIDE, CARBON DIOXIDE AND VARIOUS HYDROCARBONS
HAZARDOUS POLYMERIZATION - WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE - MAY CAUSE DIZZINESS OR NAUSEA.
SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE - SKIN: MAY CAUSE IRRITATION OR BURNING SENSATION.
EYES: PRIMARY IRRITATION
INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE - N/A
SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE - MAY CAUSE IRRITATION OR BURNING SENSATION.
HEALTH HAZARDS (ACUTE AND CHRONIC) - INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT, OR NERVOUS SYSTEM DEPRESSION (CHARACTERIZED BY HEADACHE, DIZZINESS, NAUSEA OR POSSIBLE UNCONSCIOUSNESS). SKIN OR EYE CONTACT: PRIMARY IRRITATION. PROLONGED OR REPEATED CONTACT TO SKIN MAY CAUSE DERMATITIS - EXERCISE DUE CARE
CARCINOGENICITY: NONE KNOWN NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO
TERATOGENICITY - N/A MUTAGENICITY - N/A TOXICOLOGICALLY SYNERGISTIC PRODUCT - N/A
MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE - NONE KNOWN
EMERGENCY AND FIRST AID PROCEDURES - VAPORS: REMOVE FROM EXPOSURE AND RESTORE BREATHING, SEEK MEDICAL ATTENTION
SPLASH: (SKIN) WASH AFFECTED AREA, REMOVE CONTAMINATED CLOTHING, SEE PHYSICIAN IF ANY IRRITATION PERSISTS.
SPLASH: (EYES) FLUSH IMMEDIATELY WITH WATER FOR 15 MINUTES AND TAKE TO A PHYSICIAN.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED - REMOVE ALL SOURCES OF IGNITION: FLAMES, SPARKS, STATIC ELECTRICITY & ELECTRICAL. VENTILATE AREA AND SOAK UP WITH INERT ABSORBENT USING NON-SPARKING TYPE TOOLS.
WASTE DISPOSAL METHOD - DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING - DO NOT STORE ABOVE 120° F/48.9° C. DO NOT STORE OR USE NEAR HEAT, SPARKS, OR FLAME.
OTHER PRECAUTIONS - DO NOT GET IN EYES. DO NOT BREATHE VAPORS. AVOID SKIN CONTACT. DO NOT TAKE INTERNALLY. SMOKING WHILE USING THIS PRODUCT MUST BE STRICTLY PROHIBITED. IN ADDITION TO ALL OTHER HAZARDS AND PRECAUTIONS - DUST FROM SANDING THE DRY PAINT FILMS SHOULD BE TREATED AS A NUISANCE DUST WITH A TLV OF 10/CUBIC METER.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION - OUTDOORS: APPROVED PARTICULATE FILTER TO REMOVE ANY AIRBORNE OVERSPRAY. IN RESTRICTED AREAS WITH POOR VENTILATION AND CLOSE TO THE T.L.V., USE A NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE.
VENTILATION - ALL APPLICATION AREAS SHOULD BE ADEQUATELY VENTILATED IN ORDER TO KEEP THE ITEMS IN SECTION II BELOW THEIR EXPOSURE LIMITS.
PROTECTIVE GLOVES - IMPERVIOUS GLOVES (NATURAL RUBBER) ARE RECOMMENDED TO PREVENT SKIN CONTACT.
EYE PROTECTION - SAFETY GLASSES WITH SIDE SHIELDS ARE RECOMMENDED TO PREVENT EYE CONTACT.
OTHER PROTECTIVE CLOTHING OR EQUIPMENT - IMPERVIOUS APRON IS RECOMMENDED TO PREVENT SKIN CONTACT. EYE WASH FOUNTAIN AND SAFETY SHOWER.
WORK/HYGIENIC PRACTICES - AVOID PROLONGED OR REPEATED CONTACT. DO NOT BREATHE VAPORS. WASH CONTAMINATED CLOTHING PRIOR TO RE-USE.

SECTION IX - DISCLAIMER

DISCLAIMER - THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO.
NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.