



# Material Safety Data Sheet

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know.

The following material safety data sheet covers the hazardous ingredients associated with more than one color aerosol product. As per 29 CFR 1900.1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

**PRODUCT NAME:** Aerosol Survey Marking Paint

Non-Fluorescent Colors		Fluorescent Colors	16 oz. I.A.C.		High Delivery	Metallic
201 Red	207 White	220 Red	261S Red	270S Fluorescent Red	281 Red	210 Silver
202 Yellow	208 Hi Visibility Yellow	222 Orange	262S Yellow	272S Fluorescent Orange	282 Yellow	
203 Blue	209 Light Blue	224 Green	263S Blue	274S Fluorescent Green	288 Fluorescent Orange	
204 Green	212 Purple	226 Yellow	265S Orange	275S Fluorescent Red/Orange		
205 Orange	213 Brown	227 Blue	267S White	279S Fluorescent Pink		
206 Black		229 Pink				
		230 Red/Orange				

**SECTION I - MANUFACTURER IDENTIFICATION**

**MANUFACTURER'S NAME:** Aerove Industries, Inc. **ADDRESS:** 1198 Mark Circle, Gardnerville, NV 89410  
**INFORMATION PHONE:** 775-782-0100 **EMERGENCY PHONE:** 1-800-424-9300  
**DATE REVISED:** 01-21-04 **REASON REVISED:** Updated

**SECTION II: HAZARDOUS INGREDIENTS / SARA III INFORMATION / OCCUPATIONAL EXPOSURE LIMITS**

Hazardous Component	Hydrocarbon Propellant	Hexane	Xylene	Aliphatic Petroleum Distillates	Ethyl Acetate	Acetone	Glycol Ether EB Acetate	VM&P Naphtha	Aliphatic Hydrocarbon	n-Butyl Acetate
CAS #	68476-86-8	110-54-3	1330-20-7	64742-88-7	141-78-6	67-64-1	112-07-2	64742-89-8	64742-47-8	123-86-4
OSHA PEL (TWA)	1000 ppm	500 ppm	100 ppm	100 ppm	400 ppm	1000 ppm	N / AV	300 ppm	N / AV	150 ppm
ACGIH TLV (TWA)	1000 ppm	50 ppm (skin)	100 ppm	100 ppm	400 ppm	500 ppm	N / AV	400 ppm	N / AV	150 ppm
LD50 Species & Route	N / AV	2870 mg/kg (Rat-Oral)	4300 mg/kg (Rat-Oral)	N / AV	N / AV	5800 mg/kg (Rat-Oral)	N / AV	N / AV	N / AV	N / AV
LC50 Species	N / AV	N / AV	6700 ppm 4 hr (Rat)	N / AV	N / AV	21,000 ppm 8 hr (Rat)	N / AV	N / AV	N / AV	N / AV
SARA 313 Listed	no	yes	yes	no	no	no	yes	no	no	no
	wt %	wt %	wt %	wt %	wt %	wt %	wt %	wt %	wt %	wt %

**Non-Fluorescent Colors**

10 - 30	7 - 13	5 - 10	1 - 5	1 - 5	3 - 7	1 - 5			
---------	--------	--------	-------	-------	-------	-------	--	--	--

**Fluorescent Colors**

10 - 30	7 - 13		1 - 5				7 - 13		
---------	--------	--	-------	--	--	--	--------	--	--

**Metallic, 210 Silver**

15 - 40		7 - 13			30 - 60		5 - 10	5 - 10	1 - 5
---------	--	--------	--	--	---------	--	--------	--------	-------

17A

**SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS**

**BOILING POINT:** N / AP **SPECIFIC GRAVITY (H20=1):** 0.8 to 0.9  
**VAPOR DENSITY:** Heavier than air **SOLUBILITY IN WATER:** Partially  
**EVAPORATION RATE:** Faster than n-Butyl Acetate **APPEARANCE AND ODOR:** Opaque liquid with hydrocarbon odor

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

**FLASH POINT:** < 0° F (-18° C) **METHOD USED:** Estimated **FLAMMABLE LIMITS - LEL:** 0.9% **UEL:** 15.0%  
**EXTINGUISHING MEDIA:** Carbon dioxide, dry chemical, water spray.  
**SPECIAL FIRE FIGHTING PROCEDURES:** Use water spray to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.  
**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Treat as cylinders of compressed gas. Closed containers may rupture due to pressure build up from extreme temperature.  
**FLAMMABILITY:** Flammable aerosol under conditions of sparks, flame, or hot surfaces.  
**SENSITIVITY TO IMPACT:** Do not puncture **SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

**SECTION V - REACTIVITY DATA**

**STABILITY:** Stable **CONDITIONS TO AVOID:** Open flames, sparks, electrical arcs.  
**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents.  
**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon Monoxide, Carbon Dioxide.  
**HAZARDOUS POLYMERIZATION:** Will not occur

**SECTION VI - HEALTH HAZARD DATA**

**INHALATION:** Respiratory tract irritant. May cause dizziness, light-headedness and / or headaches.  
**SKIN CONTACT:** Prolonged or repeated contact may cause irritation and dermatitis.  
**EYE CONTACT:** Painful with slight to moderate irritation.  
**SKIN ABSORPTION:** Not likely to be absorbed in toxic amounts under normal use.  
**INGESTION:** Not likely to be harmful in small amounts but swallowing large amounts may be harmful.  
**CARCINOGENICITY:** The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.  
**TERATOGENICITY:** Not established **MUTAGENICITY:** Not established  
**MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE:** Not established  
**EMERGENCY AND FIRST AID PROCEDURES:** INHALATION - Remove from exposure, seek medical attention if signs/symptoms persist.  
 SKIN - Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.  
 EYES - Flush immediately with water for 15 minutes, seek medical attention if irritation persists.  
 INGESTION - Do NOT induce vomiting. Drink plenty of water, seek medical attention.

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.  
**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120° F (49° C). Do not store or use near heat, sparks or flame.  
**OTHER PRECAUTIONS:** Do not get in eyes or on skin. Do not breathe vapors, take internally or smoke while using this product.

**SECTION VIII - CONTROL MEASURES**

**RESPIRATORY PROTECTION:** In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator. For concentrations above the TLV (as defined in Section II), use a positive air supplied respirator.  
**VENTILATION:** General ventilation to maintain exposure limits below TLV's as defined in Section II.  
**PROTECTIVE GLOVES:** Chemical resistant gloves such as Neoprene or Nitrile rubber.  
**EYE PROTECTION:** Safety glasses or goggles.  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Not established.  
**WORK / HYGIENIC PRACTICES:** Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

**SECTION IX - DISCLAIMER**

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.

# Aerove Survey Marking Paint (Regular Colors) - Bulk



# Material Safety Data Sheet

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

The following material safety data sheet covers the hazardous ingredients associated with more than one color bulk product. As per 29 CFR 1900.1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following Aerove-Pacific bulk products.

## MARKING PAINT - REGULAR COLORS

201 RED	204 GREEN	207 WHITE	210 SILVER
202 YELLOW	205 ORANGE	208 HI VISIBILITY YELLOW	212 PURPLE
203 BLUE	206 BLACK	209 LIGHT BLUE	213 BROWN

**PRODUCT NAME:** MARKING PAINT - ALL REGULAR COLORS    **PRODUCT CODE:** 17B    **HMIS CODES:** H 2 F 3 R 0 P X

## SECTION I - MANUFACTURER IDENTIFICATION

**MANUFACTURER'S NAME:** Aerove-Pacific Company, Inc.    **ADDRESS:** 1198 Mark Circle, Gardnerville, NV 89410  
**INFORMATION PHONE:** 775-782-0100    **EMERGENCY PHONE:** 1-800-424-9300  
**DATE REVISED:** 03-14-02    **REASON REVISED:** Updated

## SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
*XYLENE (CAS 1330 20 7)	44	100 PPM	100 PPM		4300 mg / kg RAT (ORAL)	6700 PPM; 4 hr RAT (INHA)
*ETHYL BENZENE (CAS 100 41 4)	5	100 PPM	100 PPM	N/A	3500 mg / kg RAT (ORAL)	N/A
MINERAL SPIRITS (CAS 8052 41 3)	5	100 PPM	100 PPM		N/A	N/A
*GLYCOL ETHER EB ACETATE (CAS 112 07 2)	2	N/A	N/A	N/A	N/A	N/A
<b>210 SILVER ALSO INCLUDES THE FOLLOWING:</b>						
ACETONE (CAS 67 64 1)	< 5 %	750 PPM	750 PPM		9750 mg / kg RAT (ORAL)	6700 PPM / 4 hr RAT (INHA)

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

**NOTE:** N/A applies to not available or not applicable

**PRODUCT CODE:** 17B

## SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

**BOILING POINT:** 149° to 289°F (65° to 142.8° C)    **SPECIFIC GRAVITY (H20=1):** 1.1    **COEFFICIENT OF WATER/OIL DIST:** N/A  
**ODOR THRESHOLD:** N/A    **VAPOR DENSITY:** Heavier than air    **SOLUBILITY IN WATER:** Negligible  
**EVAPORATION RATE:** Slower than n-Butyl Acetate    **APPEARANCE AND**    **ODOR:** Opaque Liquid / Solvent Based Odor  
**COATING V.O.C. :** 6.24 lbs / Imp gal    5.20 lbs / US gal    523 gms / ltr    **FREEZING POINT:** N/A    **pH:** N/A

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT:** 59° to 74°F (15° to 23.3° C)    **METHOD USED:** Estimated  
**FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER:** 0.7%    **UPPER:** 7.0%  
**EXTINGUISHING MEDIA:** Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog  
**SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be ineffective, but water spray may be used to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.  
**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may rupture due to pressure build up from extreme heat or fire.  
**FLAMMABILITY:** Yes - Flammable liquid under conditions of sparks, flame, or hot surfaces.  
**SENSITIVITY TO IMPACT:** Do not puncture    **SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

## SECTION V - REACTIVITY DATA

**STABILITY:** Stable    **CONDITIONS TO AVOID:** High temperatures  
**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents  
**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon Monoxide and Carbon Dioxide  
**HAZARDOUS POLYMERIZATION:** Will not occur

## SECTION VI - HEALTH HAZARD DATA

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause dizziness or nausea.  
**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** SKIN - May cause irritation or burning sensation.  
EYES - Primary irritation.  
**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause irritation or burning sensation.  
**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** N/A  
**HEALTH HAZARDS (ACUTE AND CHRONIC):** INHALATION - Anesthetic. Irritation of the respiratory tract, or nervous system depression (characterized by headache, dizziness, nausea or possible unconsciousness). SKIN OR EYE CONTACT - Primary irritation. Prolonged or repeated contact to skin may cause dermatitis - exercise due care.  
**CARCINOGENICITY:** None known    **NTP?** No    **IARC MONOGRAPHS?** No    **OSHA REGULATED?** No  
**TERATOGENICITY:** N/A    **MUTAGENICITY:** N/A    **TOXICOLOGICALLY SYNERGISTIC PRODUCT:** N/A  
**MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE:** None known  
**EMERGENCY AND FIRST AID PROCEDURES:** VAPORS - Remove from exposure and restore breathing, seek medical attention.  
SPLASH - (SKIN) Wash affected area, remove contaminated clothing, see physician if any irritation persists.  
SPLASH - (EYES) Flush immediately with water for 15 minutes and take to a physician.

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition - Flames, sparks, static electricity & electrical. Ventilate area, avoid run off into sewer by diking, and soak up with inert absorbent using non-sparking type tools.  
**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120° F / 49° C. Do not store or use near heat, sparks or flame.  
**OTHER PRECAUTIONS:** Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strictly prohibited. In addition to all other hazards and precautions - dust from sanding the dry paint films should be treated as a nuisance dust with a **TLV of 10mg/cubic meter.**

## SECTION VIII - CONTROL MEASURES

**RESPIRATORY PROTECTION:** Outdoors - Recommend an approved mechanical particulate filter to remove any airborne overspray. In restricted areas with poor ventilation, use a NIOSH approved Organic Cartridge Respirator. For concentrations above the exposure limit, use a positive air supplied respirator.  
**VENTILATION:** All application areas should be adequately ventilated in order to keep the items in SECTION II below their exposure limits.  
**PROTECTIVE GLOVES:** Impervious gloves (natural rubber) are recommended to prevent skin contact.  
**EYE PROTECTION:** Safety glasses with side shields are recommended to prevent eye contact.  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Impervious apron (natural rubber) is recommended to prevent skin contact. Eye wash fountain and safety shower.  
**WORK / HYGIENIC PRACTICES:** Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

## SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.

# AerVOE Survey Marking Paint (Fluorescent Colors) - Bulk



# Material Safety Data Sheet

TO: MSDS USERS

Please find below the material safety data sheet as per your request.

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

The following material safety data sheet covers the hazardous ingredients associated with more than one color bulk product. As per 29 CFR 1900.1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following AerVOE-Pacific bulk products.

## MARKING PAINT - FLUORESCENT COLORS

220 RED	224 GREEN	229 PINK
222 ORANGE	226 YELLOW	230 RED/ORANGE
	227 BLUE	

**PRODUCT NAME:** MARKING PAINT - ALL FLUORESCENT COLORS **PRODUCT CODE:** 17B2 **HMIS CODES:** H 2 F 3 R 0 P X

## SECTION I - MANUFACTURER IDENTIFICATION

**MANUFACTURER'S NAME:** AerVOE-Pacific Company, Inc.  
**INFORMATION PHONE:** 775-782-0100  
**DATE REVISED:** 03-14-02

**ADDRESS:** 1198 Mark Circle, Gardnerville, NV 89410  
**EMERGENCY PHONE:** 1-800-424-9300  
**REASON REVISED:** Updated

## SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
*XYLENE (CAS 1330 20 7)	23	100 PPM	100 PPM		4300 mg / kg RAT (ORAL)	6700 PPM; 4 hr RAT (INHA)
*ETHYL BENZENE (CAS 100 41 4)	4	100 PPM	100 PPM	N/A	3500 mg / kg RAT (ORAL)	N/A
PETROLEUM NAPHTHA  (CAS 64742-89-8)	16	400 PPM	400 PPM		> 7.10 g / kg RAT (ORAL) > 2.84 g / kg RAT (DERMAL)	15,000 PPM / 4 hr RAT (INHA)

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

**NOTE:** N/A applies to not available or not applicable

**PRODUCT CODE:** 17B2

## SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

**BOILING POINT:** 222° to 278°F / 106° to 137° C **SPECIFIC GRAVITY (H2O=1):** 1.2 **COEFFICIENT OF WATER/OIL DIST:** N/A  
**ODOR THRESHOLD:** N/A **VAPOR DENSITY:** Heavier than air **SOLUBILITY IN WATER:** Negligible  
**EVAPORATION RATE:** Slower than n-Butyl Acetate **APPEARANCE AND ODOR:** Opaque Liquid / Solvent Based Odor  
**COATING V.O.C. :** 5.08 lbs / Imp gal 4.23 lbs / US gal 507 gms / ltr **FREEZING POINT:** N/A **pH:** N/A

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT:** 20° F / -7° C **METHOD USED:** Estimated **FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER:** 1.0% **UPPER:** 8.0%  
**EXTINGUISHING MEDIA:** Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog  
**SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be ineffective, but water spray may be used to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.  
**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may rupture due to pressure build up from extreme heat or fire.  
**FLAMMABILITY:** Yes - Flammable liquid under conditions of sparks, flame, or hot surfaces.  
**SENSITIVITY TO IMPACT:** Do not puncture **SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

## SECTION V - REACTIVITY DATA

**STABILITY:** Stable **CONDITIONS TO AVOID:** High temperatures  
**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents  
**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon Monoxide and Carbon Dioxide  
**HAZARDOUS POLYMERIZATION:** Will not occur

## SECTION VI - HEALTH HAZARD DATA

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause dizziness or nausea.  
**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** SKIN - May cause irritation or burning sensation.  
EYES - Primary irritation.  
**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** May cause irritation or burning sensation.  
**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** N/A  
**HEALTH HAZARDS (ACUTE AND CHRONIC):** INHALATION - Anesthetic. Irritation of the respiratory tract, or nervous system depression (characterized by headache, dizziness, nausea or possible unconsciousness). SKIN OR EYE CONTACT - Primary irritation. Prolonged or repeated contact to skin may cause dermatitis - exercise due care.  
**CARCINOGENICITY:** None known **NTP? No** **IARC MONOGRAPHS? No** **OSHA REGULATED? No**  
**TERATOGENICITY:** N/A **MUTAGENICITY:** N/A **TOXICOLOGICALLY SYNERGISTIC PRODUCT:** N/A  
**MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE:** None known  
**EMERGENCY AND FIRST AID PROCEDURES:** VAPORS - Remove from exposure and restore breathing, seek medical attention.  
SPLASH - (SKIN) Wash affected area, remove contaminated clothing, see physician if any irritation persists.  
SPLASH - (EYES) Flush immediately with water for 15 minutes and take to a physician.

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition - Flames, sparks, static electricity & electrical. Ventilate area, avoid run off into sewer by diking, and soak up with inert absorbent using non-sparking type tools.  
**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120° F / 49° C. Do not store or use near heat, sparks or flame.  
**OTHER PRECAUTIONS:** Do not get in eyes. Do not breathe vapors. Avoid skin contact. Do not take internally. Smoking while using this product must be strictly prohibited. In addition to all other hazards and precautions - dust from sanding the dry paint films should be treated as a nuisance dust with a **TLV of 10mg/cubic meter.**

## SECTION VIII - CONTROL MEASURES

**RESPIRATORY PROTECTION:** Outdoors - Recommend an approved mechanical particulate filter to remove any airborne overspray. In restricted areas with poor ventilation, use a NIOSH approved Organic Cartridge Respirator. For concentrations above the exposure limit, use a positive air supplied respirator.  
**VENTILATION:** All application areas should be adequately ventilated in order to keep the items in SECTION II below their exposure limits.  
**PROTECTIVE GLOVES:** Impervious gloves (natural rubber) are recommended to prevent skin contact.  
**EYE PROTECTION:** Safety glasses with side shields are recommended to prevent eye contact.  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Impervious apron (natural rubber) is recommended to prevent skin contact. Eye wash fountain and safety shower.  
**WORK / HYGIENIC PRACTICES:** Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

## SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.