

Complete Repair

Complete Repair

MSDS

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

US Department of Labor

Occupational Safety and Health Administration
Form Approved, OMB No. 1218-0072

Section I: Information

JET SET COMPLETE REPAIR

Emergency Telephone Number, Jet Set Cement Corp. (510) 632-7800. (877) 239-7800

Date prepared: January 28, 2000

Section II: Hazardous Ingredients/Identity Information

Common Name(s)	CAS #	OSHA PEL	ACGIH TLV	Other	%
Calcium Salts - Cement	65997-15-1	10 mg/m3	10 mg/m3	None	N/A
Calcium Sulphate Hemihydrate	7778-18-9	5 mg/m3	10 mg/m3	None	N/A
Silica Sand	14808-60-7	0.1 mg/m3	0.1 mg/m3	None	N/A

15.0 mg/m3 TOTAL DUST

Section III - Physical/Chemical Characteristics

Bolling Point:	N/A	Specific Gravity (H2O = 1)	3.00
Vapor Pressure (mm Hg):	N/A	Melting Point:	N/A
Vapor Density (air = 1):	N/A	Evaporation Rate:	N/A
Solubility in Water:	Slight (0.1 - 1%)		
Appearance and Odor:	Grey (or white) powder, Odorless		

Section IV - Fire and Explosion Hazard

Flash Point (Method Used)	N/A
Flammable Limits:	LEL N/A UEL N/A
Extinguishing Media:	None (Not Combustible)
Special Fire Fighting Procedures:	None (Not Combustible)
Unusual Fire and Explosion Hazards:	None (Not Combustible)

Section V - Reactivity Data

Stability: STABLE Conditions to Avoid: NONE

http://jetsetcement.com/complete_repair.htm

4/4/01

