

MATERIAL SAFETY DATA SHEET

MSDS Name: POLYSEAMSEAL TUB & TILE Adhesive Caulk
 MSDS Number: sD11515
 Version Number
 MSDS Date: APR-22-1999
 Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: POLYSEAMSEAL TUB & TILE Adhesive Caulk
 Hazard Rating: Health: 1 Fire: 0 Reactivity: 0 PPI: B

Company Identification: OSI SEALANTS, INC.
 7405 PRODUCTION DRIVE
 MENTOR OH 44060

Contact: Safety Officer
 Telephone/Fax: (440) 255-8900 (440) 974-2395
 Emergency Phone (24 hour) CHEMTREC
 (800) 424-9300
 Chemtrec (outside-USA) (703) 527-3887
 Preparer T.F.Barr
 Sr. R. & D. Chemist

Product Class CAULK
 Trade Name POLYSEAMSEAL
 Product Code ---

SECTION II - INGREDIENT AND HAZARD INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
N-Butyl Acetate	0123-86-4	< 5.0	Y
Titanium Dioxide **	13463-67-7	< 2.0	Y

Ingredient Notes:

**The main hazard for Titanium Dioxide is dust inhalation. Because of its incorporation into the caulk, exposure by inhalation is unlikely.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: High viscosity caulk
 Appearance/Color: White & colors
 Odor: Banana odor
 Solubility (in water): yes
 pH Value, +/- .3: 7.5
 Boiling Range: 212.0F (100.0C)
 Vapor Pressure (mmHg): 15.0 @ 68.0F (20.0C)

MATERIAL SAFETY DATA SHEET

MSDS Name: POLYSEAMSEAL TUB & TILE Adhesive Caulk
MSDS Number: sD11515
Version Number
MSDS Date: APR-22-1999
Page Number: 2

Evaporation Rate: 0.5 times Slower than n-Butyl Acetate

Vapor Density: Heavier than air

% Volatile, Weight approx. 30.%
% Volatile, Volume approx. 45.%
Specific Gravity: 1.245
VOC (less H2O or exempt) 93 Gr/L
Heavy Elements (ppm) 0.

NOTE:

Odor : Mild acrylic odor. Freeze Point : 32 Deg F

SECTION IV - FIRE FIGHTING MEASURES (Flash,UEL,LEL for solvent only)

Flammability Class N/A
Flash Range: Not Available
Explosive Range (LEL/UEL): Not Applicable

EXTINGUISHING MEDIA:

Dry chemical -- Carbon Dioxide -- Foam -- Water Fog
Will not burn in wet state.

SPECIAL FIRE-FIGHTING PROCEDURES:

Water may be used to cool and protect exposed containers.
Caution should be taken because uncured material is watersoluble

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may burst when exposed to extreme heat or fire.

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY:

ENTRY THROUGH...

Inhalation? Yes | Skin? Yes | Ingestion? Yes

TARGET ORGANS... --Butyl Acetate: Eyes

-- Titanium Dioxide: Eyes, Skin, Lung

Overexposure -- Butyl Acetate: Eye contact causes severe irritation. Vapors may be irritating and cause dizziness, headache, nausea, vomiting and narcosis.

-- Titanium Dioxide: Respiratory Tract Irritant(Dust only)

CARCINOGENICITY...NTP? N/E| IARC NO | OSHA? N/E

EFFECTS OF OVEREXPOSURE

MATERIAL SAFETY DATA SHEET

MSDS Name: POLYSEAMSEAL TUB & TILE Adhesive Caulk
MSDS Number: sD11515
Version Number
MSDS Date: APR-22-1999
Page Number: 3

Inhalation: May irritate respiratory tract.
Skin/Eye Contact: May cause irritation.
Ingestion: Swallowing large amounts may cause nausea,
vomiting or diarrhea.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain, nervous system, liver or kidney damage or may cause cardiac arrhythmia. INTENTIONAL misuse of this product by deliberately inhaling its vapors may be harmful or fatal.

FIRST AID MEASURES

Inhalation: If affected by inhalation, remove to fresh air.
Eye Contact: Flush with water for at least 15 minutes, and get prompt medical attention.
Skin Contact: Wash skin thoroughly with soap and water.
Ingestion: Drink copious amounts of water. Induce vomiting and call a physician.

N/A= Not applicable N/AV=Not available N/E, N/est=Not established

SECTION VI - STABILITY AND REACTIVITY

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY:

None

CONDITIONS TO AVOID:

None

HAZARDOUS DECOMPOSITION PRODUCTS:

May produce oxides of carbon and oxides of nitrogen when burned.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

STEPS TO BE TAKEN IN CASE OF SPILL:

Wear appropriate protective clothing. Add dry absorbent and shovel or sweep up. Place in an appropriate container and seal.

WASTE DISPOSAL METHOD:

Dispose of in accordance with Federal, State, and Local regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL

PROTECTION-----
MATERIAL SAFETY DATA SHEET

MSDS Name: POLYSEAMSEAL TUB & TILE Adhesive Caulk
 MSDS Number: sD11515
 Version Number
 MSDS Date: APR-22-1999
 Page Number: 4

Occupational Exposure Limits	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
N-Butyl Acetate	150.00 PPM	N/est	200.00 PPM	200.00 PPM	150.00 PPM
Titanium Dioxide **	10.00 mg/F3	N/est	N/est	N/est	15.00 mg/F3

RESPIRATORY PROTECTION:

NIOSH approved respirators recommended if vapors and mists are generated.

VENTILATION:

Local exhaust is recommended for safe practice.

PROTECTIVE CLOTHING:

Rubber gloves and impervious clothing should be worn to prevent repeated skin contact.

EYE PROTECTION:

Splashproof goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep from freezing. Keep away from heat.

Keep out of the reach of children ;

Keep containers closed when not in use

Avoid prolonged or repeated contact with skin.

SECTION IX - TRANSPORT INFORMATION:

DOT CLASSIFICATIONS FOR CARTRIDGES 10 or 29 oz.

DESCRIPTION: Non-hazardous

DOT CLASSIFICATIONS for 1 GALLON or larger CONTAINERS

DESCRIPTION: Non-hazardous

Caulking type product

SECTION X - REGULATORY INFORMATION:

The components fit the EPA Hazard Category definition of

MATERIAL SAFETY DATA SHEET

MSDS Name: POLYSEAMSEAL TUB & TILE Adhesive Caulk
MSDS Number: sD11515
Version Number
MSDS Date: APR-22-1999
Page Number: 5

Immediate (Acute) and Delayed (Chronic) Health Hazards
under SARA Sections 311, 312.

All chemical substances are TSCA listed.

SARA Section 313 toxic chemicals: NONE above the de minimis
reporting thresholds.

California PROP.65 Chemicals: none known

DISCLAIMER:

The information contained herein is based on data available as of
the date of preparation of this MSDS and which we believe to be
reliable. However, no warranty is expressed or implied regarding
the accuracy of the data. We shall not be responsible for the use
of this information, or of any product, method, or apparatus men-
tioned, and the user must make his own investigation to determine
the suitability of the information or products for his particular
purpose, for the protection of the environment, and the health and
safety of the users of this material.

Last Page

