


GIUY**UNITEX**

3701 GARDNER, KANSAS CITY, MISSOURI 64120, 816-231-7700

MATERIAL SAFETY DATA SHEET

Complies with OSHA's Hazard Communication Standard, 29 CFR 1910.1200

IDENTITY As Used on Label and List:PRO-POXY 300SECTION I

Manufacturer's Name: UNITEX
3701 Gardner
Kansas City, MO 64120

Emergency Telephone No.: 800-424-9300
Telephone No.: 816-231-7700
Date Prepared: 01-28-94

Section II-Hazardous Ingredients/Identify Information:

PRODUCT CLASS: Epoxy
FORMULATION IDENTIFICATION: Adhesive
OSHA PEL: Not Established

ACGIH TLV: Not Established

COMPONENT A: Contains hazardous material as defined by OSHA (1910.1200).
Identity withheld as trade secret. Material is a sensitizer. Does not contain reportable
quantities of any substance listed under SARA Title III Section 313.

COMPONENT B: Contains amines which are hazardous materials as defined by OSHA (1910.1200).
Identity withheld as a trade secret. Material is corrosive. Can cause severe burns if
used improperly, can cause allergic reactions. Does not contain reportable quantities
of any substance listed under SARA Title III Section 313.

TRANSPORTATION INFORMATION: DOT classification: ALKYLAMINES, n.o.s.
SHIPPING # UN 2735

SECTION III - Physical/Chemical Characteristics:

Boiling Point:	A: N/E	Specific Gravity:	A: 1.465
	B: N/E		B: 1.58
Vapor Pressure (mm Hg):	N/E	Melting Point:	A: N/E
			B: N/E
Vapor Density (Air = 1):	A: > 1	Evaporation Rate (ETHER = 1)	A: > 1
	B: > 1		B: > 1
Solubility in Water:	Insoluble		
Appearance and Odor:	A: White gel, mild odor.	B: Gray gel, strong odor.	

SECTION IV - Fire and Explosion Hazard Data:

Flash Point (Method Used): A: > 200°F.
B: > 200°F.

Flammable Limits: LEL: N/A UEL: N/A

Extinguishing Media: Foam, CO₂, Water Fog

Special Fire Fighting Procedures: None

Unusual Fire and Explosion Hazards: None. Avoid breathing Smoke.

SECTION V - Reactivity Data:

Stability: Stable

Incompatibility (Materials to Avoid): Strong Oxidizers, Strong Bases

Hazardous Decomposition or Byproducts: CO, CO₂, NOX

Hazardous Polymerization: None

Conditions to Avoid: None

Conditions to Avoid: Fires when curing.

SECTION VI - HEALTH HAZARD DATA:

Cardiogenicity: No NTP? No IARC? No OSHA Regulated? No

FASTENAL PRO-POXY 300 FAST**SECTION VI - HEALTH HAZARD DATA:**

Carcinogenicity: No NTP? No IARC? No OSHA Regulated? No

Effects and Hazards of Overexposure (Acute and Chronic):

Effects and Hazards of Overexposure (Acute and Chronic):		
Eye:	Component A:	Will produce irritation, sensitization.
	Component B And Mixture:	Causes severe burns.
Skin:	Component A:	Will produce irritation, sensitization.
	Component B And Mixture:	Causes severe burns.
Inhalation:	Component A:	Will produce irritation, sensitization.
(breathing)	Component B And Mixture:	Causes severe burns.
Ingestion:	Component A:	Will produce irritation, sensitization.
(swallowing)	Component B And Mixture:	Causes severe burns.

Emergency and First Aid Procedures:

Remove any contaminated clothing.

Eye: Flush immediately with large amounts of water for at least 15 minutes; contact physician immediately.

Skin: Remove epoxy from skin immediately with a dry cloth or paper towel. Wash area of contact thoroughly with soap and water. SOLVENTS SHOULD NOT BE USED because they carry the irritant into the skin.

Inhalation: If respiratory irritation occurs, go to fresh air. Flood work area with fresh air if irritation continues, seek medical attention.

Ingestion: Not expected. Contact medical help immediately. Untrained first aid personnel should not attempt to administer first aid.

Contaminated Clothing should be washed prior to re-use.

SECTION VII - Spill or Leak Procedures:

Steps to be taken in case material is leaked or spilled:

Bind with absorbent material.

Waste Disposal Method: Small Spill:

Per local, state and federal regulations.

SECTION VIII - Safe Handling and Use Information:

Respiratory Protection: Respiratory protection is required for normal use of this product. NIOSH/MSHA approved respirators should be provided and worn. All workers required to use respiratory protection should be trained in their proper selection, use and care. A written respirator program is outlined in 29 CFR 1910.134, and is required by OSHA.

Ventilation (Local Exhaust):	Recommended	Ventilation (Mechanical-General): Recommended
Ventilation (Special):	Recommended; when local and mechanical ventilation is not adequate.	
Ventilation (Other):	N/E	

Protective Gloves: Required

Eye Protection: Required

Other Protective Equipment: Recommended; splash bib with protective clothing.

Work/Hygiene Practices: Remove and wash contaminated clothing. As with all commercial and industrial products, always wash hands before eating or smoking.

SECTION IX - Special Precautions:

Precautions to be taken in handling:

Store in a cool, dry location. Do not allow the material to freeze, as product may be damaged. Store away from sparks and open flame.

Other Precautions:

None

Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof, Unitex makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Unitex be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. No representations or warranties either express or implied of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers.

N/A: Not Available

N/E: Not Established