



Consultants to the Sheet Metal Industry

MATERIAL SAFETY DATA SHEET

Section 1: Product Name: Ward Spray Type Adhesive
Product Description (product use): Adhesive

COMPANY INFORMATION

Ward Industries, Inc.
1661 Lebanon Church Road
Pittsburgh, PA 15236
Phone: 412-653-7777 or 800-466-9374
FAX: 412-653-8697

MSDS INFORMATION

Preparation Date: 2/03/98
Supersedes: N/A

Medical Emergency Phone Number: 1-888-853-1758
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Section 2: Composition/Information on Ingredients

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS). Unlisted ingredients are not "hazardous" per the OSHA standard and/or are not found on the WHMIS ingredient disclosure list.

<u>Chemical/CAS Number</u>	<u>Percent</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Residual Vinyl acetate monomer (108-05-4)	<0.5%	10 ppm	10 ppm
LD50: 2920 mg/kg (oral, rat) LC50: 2828 ppm/4h (rat)			
Vapor pressure, in mm Hg @ 20 C: 92			
OSHA, ACGIH STEL: 20 ppm			

See Section 16 for additional information.

SECTION 3: Hazards Identification

EMERGENCY OVERVIEW

No specific warnings for normal use conditions.
Possible cancer hazard. Contains a material which may cause cancer.

POTENTIAL HEALTH EFFECTS

Eyes: Eye contact with liquid product may cause irritation.

Skin: Prolonged or repeated contact with liquid product may cause irritation.

Inhalation: Exposure to vapors in poorly ventilated areas may cause irritation of the nose, throat and respiratory tract.

Ingestion: Not an anticipated route of exposure. Small amounts are not anticipated to be harmful.

Chronic: No anticipated chronic effects.

Overexposure to vinyl acetate is not expected to occur during normal handling and use of this product. Vinyl acetate has been shown to cause irritation and cancer in inhalation studies with laboratory animals. Test levels of 600 PPM caused an increase in tumors in the respiratory tract of the test animals. No tumors were observed in the animals exposed at 50 PPM or lower. There is no evidence that vinyl acetate has caused cancer in humans.

REGULATED CARCINOGEN STATUS:

Vinyl acetate is listed as a potential carcinogen by ARC.

Existing Health Conditions Affected by Exposure: No known effects on other illnesses.

Section 4: First Aid Measures

If in eye: Flush immediately with water for 15 minutes. Consult a physician if irritation persists.

If on skin: Wash affected area with soap and water. Launder contaminated clothing before reuse.

If vapors inhaled: Remove subject to fresh air.

If ingested: If person can swallow, give one glass of water or milk. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

Section 5: Fire Fighting Measures

Flash Point/Method: >200 degrees F SETA

Upper Explosive Limit/Lower Explosive Limit: Not applicable

Section 5: Fire Fight Measures (continue)

Autoignition Temperature: Not applicable

Appropriate Extinguishers: Non-flammable in liquid state; use water spray, foam, dry chemical or carbon dioxide on dried product.

Special Fire Fighting Procedures: Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

Unusual Fire and Explosion Hazards: There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.

Hazardous Combustion Product: Incomplete combustion can yield low molecular weight hydrocarbons, carbon monoxide.

Section 6: Accidental Release Measures

Spill or Leak Procedures: Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds or water systems.

Section 7: Handling and Storage

HANDLING INFORMATION

Wear appropriate protective equipment when working with this product.

STORAGE INFORMATION

Avoid temperature extremes in storage.

Consult the Technical Data Sheet for specific storage instructions.

Section 8: Exposure Controls/Personal Protection

Eye Protection: Wear safety glasses to reduce the potential for eye contact; chemical safety goggles are appropriate if splashing or dusting is likely. Have eye washes available where eye contact can occur.

Skin Protection: Prevent prolonged or repeated contact by using rubber gloves and appropriate protective clothing. Launder contaminated clothing before reuse.

Section 8: Exposure Controls/Personal Protection (continue)

Respiratory Protection: Not normally required. Use NIOSH/MSHA approved respirator if conditions warrant.

Ventilation: General dilution ventilation.

Section 9: Physical and Chemical Properties

Physical State:	Liquid
Color:	White/Clear
Odor:	Mild latex
Odor Threshold:	Not established
Weight per Gallon:	8.8 lbs.
Specific Gravity:	Not established
% Solids by Weight:	40
pH:	5.5
Boiling Range:	Greater than 200 F (93 C)
Freezing/Melting Point:	Not established
Vapor Pressure:	Not established
Vapor Density:	Not established
Evaporation Rate:	Not established
Water/Oil Partition Coefficient:	Not established
VOC, less water:	14.41 g VOC/liter or material, less water and exempt solvents (VOC theoretically determined using EPA Publication 450/3-84-019.)

Section 10: Stability and Reactivity Data

Stability: Stable

Incompatibility: Not established

Hazardous Decomposition: Not established

Hazardous Polymerization: Will not occur

Section 11: Toxicological Information

No data available.

Section 12: Ecological Information

No data available.

Section 13: Disposal Considerations

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

Section 14: Transportation Information

UNITED STATES DEPARTMENT OF TRANSPORTATION (DOT)

DOT Proper Shipping Name: WATER BASE COATING N.M.F.C. ITEM
#149980 SUB 2
DOT Hazard Class/I.D. Code: NON-HAZARDOUS
Marine Pollutants: N

It is our opinion that the information provided here may be used to transport this product in compliance with Canadian Transportation of Dangerous Goods.

INTERNATIONAL TRANSPORTATION

IATA Proper Shipping Name: Industrial Sealing Compound, Item #4730
Water Base
IATA Hazard Class: Non-Hazardous
IATA Label: None
IATA Packaging Group: NA

Section 15: Regulatory Information

FEDERAL

Toxic Substances Control Act (TSCA)

Section 4 - Test Rule

This product contains the following chemical substance (s) that is (are) subject to a Section 4 Test Rule:

79-10-7 Acrylic acid

Section 8 (b) - Inventory Status

Section 15: Regulatory Information (continue)

This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

Section 12 (b) - Export Notice Requirements

This product contains a chemical substance that is currently on the EPA's Section 12 (b) Export List. Within seven days of entering into a contract to export and certainly no later than the day of export, the agent of export must notify the EPA of their intent.

Contact the company TSCA Compliance Manager at 612-415-5858 for the identity of the Section 12 (b) chemical (s).

SARA TITLE III

Section 313: This product contains the following toxic chemical (s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Percent</u>
Vinyl acetate	108-05-4	<0.5%

STATE REGULATIONS

California Proposition 65: Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

This product contains chemical (s) known to the state of California to cause cancer (c) or reproductive (r) damage.

<0.0022% Acetaldehyde (c) 75-07-0
listed April 1, 1988

<0.0319% Formaldehyde (c) 50-00-0
listed January 1, 1988

WHMIS IDENTIFICATION/OTHER INTERNATIONAL REGULATIONS

D2A

Section 16: Additional Information

In storage, monomer vapors will migrate from the emulsion and establish an equilibrium

Section 16: Additional Information (continue)

between the headspace in the storage container and the liquid emulsion. Levels in excess of acceptable exposures can accumulate in non-vented headspaces about the emulsion. All procedures appropriate for a confined space entry should be completed prior to performing any work in a bulk storage tank.

This product contains trace amounts (less than 0.1%) of formaldehyde. Formaldehyde has been identified as an animal carcinogen. Overexposure to formaldehyde should not occur with normal handling and use.

HMIS RATING

Health-1 Flammability-0 Reactivity-0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Ward Industries, Inc. from its suppliers, and because Ward Industries, Inc. has no control over the conditions of handling and use, Ward Industries, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The consideration, and Ward Industries, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of Ward Industries, Inc. products to comply with all applicable federal, state and local laws and regulations.

